

# GA321

ø140 - ø330 mm  
ø5,5 to ø12,75"




## Technical Specifications


- Basic jaws Ø 8,5" to 12,75" ( Ø 216 to Ø 330 mm )
- Included stainless steel auxiliary jaws Ø 5,5" to 10 " ( Ø 153 to Ø 256 mm )
- Supplied with plastic protection and profile guide
- **Technology:** screw carbide inserts: 10 x faster than HSS tools. Superior service life
- Max 8 mm according to spinner\*
- **Patented System**
- **Scalability:** may be transformed into a cutting and orbital welding machine
- **Weight:** 73 kg (easy handling)




V bevel with profile guide roller



J bevel with profile guide roller



Outer profile guide system: to account for tube "out of round"



Rotation handle as standard: extends blade life and optimizes cutting quality

References	Motors	Accessories	Consumables
GA321-2	GA10-220 : 220V mono	CCPS21: support feet SAEP-00 : electric rotation autoline 121 to 321 (110 V - 230V )	PC30-08-B02: carbide inserts (*) TV-300: 30° spinner (Max 8mm) TV-375: 37.5° spinner (Max 7mm) TV-450: 45° spinner (Max 6,5mm)
GA321-1	GA10-110 :110V mono	CCSER1/CCSER2: simple/bearing stand  All motors are delivered in their individual case, including the necessary tools	TJ-100: 10° spinner with 6 rollers (Max 8mm)  All spinner are delivered with their carbide inserts mounted

