

220V - 115V



Technical Specifications

SASL161 :

115V AC single-phase + earth, 50/60Hz ,
I_{max}=28A, Max. current 110 A, Power factor:
110 A, 100%

SASL 160 :

230V AC single-phase + earth, 50/60Hz ,
I_{max}=26A, Max. current 165 A, Power factor:
100 A, 100%

- Ideal for on-site work
- welding data acquisition system

• Supplied with a memory card with 200 programs, 20 levels each

Weight:

- SASL-16xTRA: 15 kg
- SASL-16xTF : 25 kg



SD Flash card with 200 programs per card



5.7" multi-language, colour touch screen



Integrated printer

References	Accessories	Consumables
<p>220V :</p> <p>SASL-160TRA : Air-cooled orbital welding TIG power source + board SATO80M/SP</p> <p>SASL-160T : Water-cooled welding power source + board for SATF/SATO</p> <p>SASL-160TF: Water-cooled welding power source + board for wire feed for SP/SAT</p> <p>110V :</p> <p>SASL-161TRA : Air-cooled orbital welding TIG power source + board SATO80M/SP</p> <p>SASL-161T : Water-cooled welding power source + board for SATF/SATO</p> <p>SASL-161TF: Water-cooled welding power source + board for wire feed for SP/SAT</p>	<p>SACF-020: Memory card</p> <p>SALCF-020: memory card reader</p>	<p>SACW-C002: Coolant</p> <p>SIMP-02: printer spool for SASL</p>

